

Pack 076792



Pack 082984



Powered exclusively by compressed air, the ERGO LIFT 1000 ROLL can lift and manoeuvre vehicles of up to 2.5 T. With 4 support arms that swivel and lock automatically, it can be adapted to suit all chassis types. Ergonomically designed, it has a lifting height of around 1 m, so you can work upright around the vehicle to avoid fatigue.

- Super-compact: 10 cm in minimum position on the ground.
- Conforms to standard EN 1493 (load reversibility).
- Extremely useful in workshops with limited space.
- Mobile, can be manoeuvred easily with 4 wheels.




Work from a standing position to help prevent musculoskeletal injuries (MSDs).




Handle to position the support arms with an **automatic locking system** (with or without load).

Supplied with 8 rubber pads



Sturdy, highly stable, warp-resistant scissor construction.

Maintenance-free, detachable hydropneumatic pump.



All axles are fitted with bronze bushes with a **self-lubricating coating**, which require no maintenance.

Adjustable sliding skid on the support arms to leave the underbody accessible.

Hydraulic safety system with **automatic scissor** lock in the event of hose rupture.


4 large attachable wheels can be used to transform the lift into a mobile carriage, enabling the vehicle to be manoeuvred easily around the workshop.




Optional accessories



4 SUV skates
065017




Included in 082984 pack
2 ramps for electric vehicles >2.20 tonnes



2 ramps for low profile sports cars
056787



max



minimum



maximum




2.5 T



max.



max.




max.

IP



kg



product delivered on pallet

2.5 T

10 cm

95 cm

1min30

50 sec.

8 bar

102" Inch

IP54

396

437 kg (lift only)